

SAMSVARSERKLÆRING (DOP)

KAVEX PVC KLEDNING OG PROFILER

Produsent: Kestrel Building Products
Produkt: 6-7mm pvc kledning i ulike farger
Bruk: Utvendig Kledning
Standard: EN 13245-2:2008
Test laboratorium: BRE Global / Exova

Skrevet på vegne av produsent og leverandør Kestrel Building Products (EN) med referanse til Declaration of Performance (ytelseserklæring) på side 2 i dette dokument.

Ytelsen til produktet angitt ovenfor er i samsvar med de deklarererte egenskapene på side 2 i dette dokument. Denne erklæringen av ytelse er utstedt i henhold til EU Direktiv nr 305/2011, under ansvaret til produsent identifisert ovenfor.

Vedlegg:

- Declaration of performance
- Typisk CE merking

Signert for og på vegne av produsenten

Espen Thorvaldsen
Daglig Leder



Moss (NO), 09.12.2019

Billet Lane
 Normanby Enterprise Park
 Scunthorpe
 North Lincs
 DN15 9YH
 United Kingdom

Declaration of Conformity

BS EN 13245-2: 2008

21- Internal / External Wall and Ceiling finishes

Table A

PRODUCT DESCRIPTION	FINISHES
6 & 7mm PVC-UE Cladding with PVC-U skin	(BW, 33, I), (DW, 22), (W) 1015, (9001, CR), 7035, X002, STONE, (ENVGR, ABIGR), ABICR, X004, X005, *X009.

Intended Use: Internal and External

Assessment and Verification of Constancy of Performance: System 3

Notified Laboratory - REACTION TO FIRE: BRE Global, Watford, Herts, WD25 9XX.
 *EXOVA Warringtonfire, WA1 2DS

Table B


ESSENTIAL CHARACTERISTIC	PERFORMANCE
Reaction to Fire	D-s3, d2/AVM
Release of Dangerous Substances	NPD
Mechanical Resistance	(23,03)
Resistance to Fixings	see installation instructions
Durability	(A.2)

The performance of the products identified in Table A is in conformity with the declared performance in Table B.

The Declaration of Performance is issued under the sole responsibility of Specialist Building Products Limited trading as KestrelBCE.

Tony Williams - Operations Director

United Kingdom - 26/02/2018

 _____
 SIGNATURE



Pack: 1 OF 1

19336
0

L13

Line13 | Length 5m. 20m (4 units) in pack

FCL3431E53

0
KESTREL

300 TEXTURED S/LAP
CLAD 5/20

DCE/300/X005



KestrelBCE
DN15 9YH
13

Reaction to fire
D-s3,d2/AVM

Durability
A2

Release of
dangerous
substances
NPD

Mechanical
resistance
23.03

Resistance to
fixings
See installation
instructions

EN 13245-2: 2008
PVC-UE Profile for internal &
external wall / ceiling finishes



Pack: 1 OF 1

19336
0

L13

Line13 | Length 5m. 25m (5 units) in pack

FCL2449ESA

0
KESTREL

150MM V-JNT
CLADDING EMBOSSED
5/25

SVE/150/1015